


INSTALLATION GUIDE FOR 9-0483

CATALYTIC OZONE DESTRUCT UNIT SPECIFICATIONS

- DEL PART NUMBER _____ 9-0483
- CAPACITY _____ OFF GAS FLOW RATES UP TO 300 CFH [142 LPM] AT 6% OZONE BY WEIGHT.
- TEMP. CONTROL _____ 150°F (66°C) CAT. BED TEMPERATURE.
- POWER _____ 120 VAC, 50/60 HZ, 50 WATTS.
- MOUNTING _____ USE EITHER SUPPLIED FLANGE OR UNISTRUT AND 4" [102] PIPE CLAMP.
- MATERIALS _____ WELDED 304 STAINLESS STEEL.

NOTE:
THE METAL OXIDE CATALYST MUST NOT BE EXPOSED TO EXCESSIVE MOISTURE.

ALL DIMENSIONS IN INCHES [MM]					APPROVALS:		DATE:		PROPERTY OF DEL OZONE THIS DOCUMENT AND THE DATA DISCLOSED HEREIN IS PROPRIETARY. IT IS NOT TO BE REPRODUCED, USED, OR OTHERWISE DISCLOSED IN WHOLE, OR IN PART, TO ANYONE, WITHOUT WRITTEN CONSENT FROM DEL OZONE.				TITLE: SPECIFICATION, CATALYTIC OZONE, DESTRUCT	
TOLERANCES: .x ± .2 .xx ± .02 .xxx ± .010 ANGLES ± 1°					DRAWN: JBELL		7/19/2013				INTERPRET DRAWING PER ANSI Y14.5-1994 SCALE: 1:8 DO NOT SCALE DRAWING		SIZE: B	
MATERIAL: SEE BOM					ENGR. APPR: Frank Martin <small>Digitally signed by Frank Martin DN: cn=Frank Martin, o=DEL Ozone, ou=Engineering, email=frankmartin@delozone.com, c=US Date: 2016.03.14 16:41:32 -0700</small>		CHECKED:		REV. SHEET: D 1 OF 1		SHEET: 1 OF 1			
FINISH: SEE BOM					Q.A. APPR:		DWG. NO: 4-1022-01							
REVISIONS														
8	7	6	5	4	3	2	1							

D
 C
 B
 A
 B FORMAT REV A