


DRAIN VALVE SPECIFICATIONS

MODEL NO.....9-1145-01

MATERIALS.....KYNAR TUBE FITTINGS
 STAINLESS STEEL "TEE"
 PVC NIPPLE
 POLYSULFONE BODY
 POLYBUTYLENE TEREPHTHALATE CAP
 STAINLESS STEEL FLOAT AND VALVE SEAT
 VITON O-RINGS

WORKING PRESSURE.....50 psi @ 100°F

ALL DIMENSIONS IN INCHES					APPROVALS:		DATE:		PROPERTY OF DEL OZONE		TITLE:	
TOLERANCES: .X ± .1 .XX ± .02 .XXX ± .010					DRAWN: J. DALLEY		12/11/2013		 advanced sanitation solutions		SPECIFICATION DRAIN VALVE, POLYSULFONE	
ANGLES ± 1°					ENGR. APPR: Frank Martin		<small>Digitally signed by Frank Martin DN: cn=Frank Martin, o=DEL Ozone, ou=Engineering, email=frankmartin@delozone.com, c=US Date: 2017.04.24 08:34:34 -0700'</small>					
MATERIAL: AS SPECIFIED					CHECKED:				INTERPRET DRAWING PER ANSI Y14.5-1994		DWG. NO:	
FINISH:					Q.A. APPR:				SCALE: 1:2 DO NOT SCALE DRAWING		REV. SHEET: B 1 OF 1	

B	REMOVE FLOW RATE	5937	04/04/2017	
A	INITIAL RELEASE	5199	12/12/2013	
ZONE	REV.	DESCRIPTION	ECN	DATE
REVISIONS				

D

C

B

A

B FORMAT REV A